



Coiled Tubing Drilling (CTD) represents a great potential for expanding production of depleted reservoir, by drilling in under balanced conditions it allows to monitor the production in real time, along with LWD analysis, bio-steering can be conducted for chasing the most attractive layers.

Challenges of UB-CTD



High

High temperature environment

Harsh for downhole equipment, the main barrier for non 100 % Metallic components



Light

WOB

Weight transfer to the bit

Overcome limited weight transmissibility and fragility of electronics toward vibration by selecting a smooth drilling process..



DD capacities for bio-steering in real-time

Capacity to adjust rapidly and efficiently to the desired trajectory and relying on responsive tool for challenging Dog-Leg Severity (DLS) requirement .



Operating in challenging environment

Being able to re-enter highly depleted reservoir and keeping the production alive while drilling by constantly managing pressure (adjusting gas/liquid ratio of injections).

Mamba Turbodrills fit to the purpose



Hydrodynamic downhole motor with the most effective conversion of hydraulics to mechanical power – delivering high RPM to the fixed blades bits ($ROP = DOC \times RPM$) - compatible for aerated drilling (multiphases fluid injected) - Flow controlled & dynamically stable BHA - Light WOB applied, reduced reactive torque - Smooth and steady surface signature due to minimal axial loads.

Reliability & Performance

Mamba Turbodrills can contribute greatly to enhancing the drilling performance of UB-CTD with real-time data analysis, hence the right choice for extending reaches & value of mature fields.

Email us :

✉ contact@mambaturbodrills.com

Follow us on LinkedIn:

 [mamba™-turbodrilling-services-mamba](https://www.linkedin.com/company/mamba-turbodrilling-services-mamba)